



Shenzhen Zecre Technology Co., LTD

ADD: 5th floor, B Building, Debaoli Industrial Park, Bantian, Longgang, Shenzhen
 TEL: 0755-28367890 FAX: 0755-28367890 Mob.: +86 186 9676 9469
 E-mail: jasmine.khang@zecre.com Website: www.zecre.com

Model: PH760

Trail camera

Key Features

Image Sensor	1/3-Inch 3-Megapixel(2592*1944) CMOS Sensor
Stand-by Time	Approx 8 months
Range of IR Flash	110 degree, Range of IR flash 20M
Trigger Times	0.2-0.6 sec super fast trigger times
HD Quality	12MP 1080P quality images & videos
Black Low Glow 940NM IR LED	28pcs The 'Black Low Glow' covert infrared flash LED provides a 65 feet flash range in the dark, which makes it a stealthy unit that does not intrude into the natural habitat.

Specification



Image sensor	1/3-Inch 3Megapixel(2592*1944) CMOS Sensor
Lens	Focal Length=7.2mm F/NO=2.8 View Angle=55°
Storage Media	SD Card, up to 32GB
Mode	PhotoVideo
Photo resolution	12.0 Mega pixels (FHD) 5.0 Mega pixels (HD) 3.0 Mega pixels (VGA)
Photo Series	1Photo 3 Photo in series
Video resolution	1080P: 1920*1080@25fps 720P: 1280*720@30fps VGA: 640*480P@30fps
File format	AVI
IR Filter:	Full Automatic IR Filter
PIR sensing angel	110°
PIR Sensing Distance	65ft/20 meters
Number of IR LED	28 IR LEDs
Max Night Vision Lighting Distance/	65ft/20 meters
Trigger Times	0.2-0.6 sec super fast trigger times
low power protection	support
Low Battery Auto Power Off	support
Triggering Interval	1min
Date Time Imprint	No
Moon Phase Imprint	No
Ambient Temperature Imprint/	No
Serial NO. Imprint	No
Exposure	Auto
Stand-by current	Lower than 0.2mA
Stand-by Time	Approx 8 months
Buid-in MIC	Yes
Interface	External: MiniUSB; SD Card Holder; 6V DC Power Jack
Fix Method	Bandage, Iron Bracket (1/4 Inch Standard Interface)
Operation Temperature	-20 - 60°C
Operating humidity	5% ~ 90%
Power Source	4-8 AA Battery DC :6V-1.5A
Water proof Standard	IP54
Security authentication	CE, ROHS
Operation Temperature	-20 - 60°C
Operating humidity	5% ~ 90%
Power Source	4-8 AA Battery DC :6V-1.5A
Language	English/Deutsch/Dansk/Suomi/Svenska/Espanol/ Francais/Italiano/Nederlands/Portugues/Chinese
Security authentication	CE,FCC, ROHS

Packing

Product size	136 x 98 x 76mm
Color box size	18*12.2*104cm
Net weight	270g
Shipment box size	20个/CT 38.2*32.3*46 cm

	Accessories list	MiniUSB Cable , Audio&Video Cable, Instructions, Iron Bracket, Bandage
--	-------------------------	--

