



Shenzhen Zecre Technology Co., Ltd

ADD: 5th floor, B Building, Debaoli Industrial Park, Bantian, Longgang, Shenzhen

TEL: 0755-28367890 FAX: 0755-28367890 Mob. :+86 186 9676 9469

E-mail:jasmine.khang@zecre.com Website: www.zecre.com

Model:PH700A

Trail camera

Key Features

Image Sensor	1/2.5-Inch 5-Megapixel(2592*1944) CMOS Sensor
Stand-by Time	Approx 8 months
Range of IR Flash	120 degree,Range of IR flash 20M
Trigger Times	0.2-0.6 sec super fast trigger times
HD Quality	12MP 1080P quality images & videos
Black Low Glow 940NM IR LED	27pcs 'Black Low Glow' covert infrared flash LED provides a 65 feet flash range in the dark, which makes it a stealthy unit that does not intrude into the natural habitat.

Specification



Image sensor	1/2.5-Inch 5Megapixel(2592*1944) CMOS Sensor
Lens	Focal Length=7.2mm F/NO=2.8 View Angle=56°
Storage Media	SD Card, up to 32GB
Mode	Photo Video Photo*Video
Photo resolution	12.0 Mega pixels 8.0 Mega pixels 5.0 Mega pixels 3.0 Mega pixels 1.0 Mega pixels
Photo Series	1Photo 2 Photo in series 3 Photo in series
Video resolution	1080P: 1920*1080@15fps 720P: 1280*720@30fps default D1: 720*480@30fps VGA: 640*480@30fps QVGA:320*240P@30fps
File format	JPEG/AVI(H.264)
IR Filter	Full Automatic IR Filter
TFT LCD Display Screen	48x35.69mm (2.36");480(RGB)*234DOT; 16M color
PIR	110°
PIR Sensing Distance	65ft/20 meters
Number of IR LED	42 IR LEDs
Max Night Vision Lighting Distance	65ft/20 meters
Trigger Times	0.2-0.6 sec super fast trigger times
Low Battery Auto Power Off	support
Triggering Interval	5second ~ 60mins (default 60 sec)
Date Time Imprint	Yes
Moon Phase Imprint	Yes
Ambient Temperature Imprint	Yes
Serial NO. Imprint	Yes
Exposure	Auto
Pass Word Set	4 bit, Digits and 26 alphabet set by yourself
Device Serial No. Set	4 bit, Digits and 26 alphabet set by yourself
Time Lapse	support
Periodic shot	0Second~24Hours
Stand-by current	Lower than 0.2mA
Stand-by Time	Approx 8 months
Built-in MIC	Yes
Built-in Speaker	Yes
Interface	External: TV out (NTSC/PAL,MiniUSB); MiniUSB; SD Card Holder; 6V DC Power Jack
Fix Method	Bandage, Iron Bracket (1/4 Inch Standard Interface)
Operation Temperature	-20 - 60°C
Operating humidity	5% ~ 90%
Power Source	4-8 AA Battery DC:6V-1.5A
Water proof Standard	IP56
Language	English/Deutsch/Dansk/Suomi/Svenska/Espanol/ Francais/Italiano/Nederlands/Portugues/Chinese
Security authentication	CE, ROHS

Packing List

Product size	136 x 98 x 76mm
Color box size	180*122*104mm
Net weight	300g

	Shipment box size	20pcs/ctn 38.5*32.5*46cm
	Accessories list	MiniUSB Cable , Audio&Video Cable, Instructions, Iron Bracket, Bandage