



Shenzhen Zecre Technology Co., LTD

ADD: 5th floor, B Building, Debaoli Industrial Park, Bantian, Longgang, Shenzhen
 TEL: 0755-28367890 FAX: 0755-28367890 Mob.:+86 186 9676 9469
 E-mail:jasmine.khang@zecre.com Website: www.zecre.com

Model: PH730 Trail camera

Highlight

| | |
|------------------------------------|--|
| Image Sensor | 1/2.5-Inch 5-Megapixel(2592*1944) CMOS Sensor |
| Stand-by Time | Approx 8 months |
| Range of IR Flash | 120 degree,Range of IR flash 20M |
| Trigger Times | 0.2-0.6 sec super fast trigger times |
| HD Quality | 12MP 1080P quality images & videos |
| Black Low Glow 940NM IR LED | The 'Black Low Glow' covert infrared flash LED provides a 65 feet flash range in the dark, which makes it a stealthy unit that does not intrude the natural habitat. |

Specification



| | |
|---|--|
| Image sensor | 1/2.5-Inch 5Megapixel (2592*1944) CMOS Sensor |
| Lens | Focal Length=7.2mm F/NO=2.8 View Angle=56° |
| Storage Media | SD Card, up to 32GB |
| Mode/工作模式 | Photo Video Photo*Video |
| Photo resolution | 12.0 Mega pixels 8.0 Mega pixels 5.0 Mega pixels 3.0 Mega pixels 1.0 Mega pixels |
| Photo Series | 1Photo 2 Photo in series |
| Video resolution | 1080P: 1920*1080@25fps 720P: 1280*720@30fps default D1: 720*480@30fps VGA: 640*480@30fps QVGA: 320*240@30fps |
| File format | JPEG/AVI(H.264) |
| IR Filter: | Full Automatic IR Filter |
| TFT LCD Display Screen: | 48x35.69mm (2.36");480(RGB)*234DOT; 16M color |
| Main PIR sensing angle | 40° |
| Side PIR sensing angle | L: 30° R: 30° |
| Total PIR sensing angle | 120° |
| PIR Sensing Distance | 65ft/20 meters |
| Number of IR LED | 42 IR LEDs |
| Max Night Vision Lighting Distance | 65ft/20 meters |
| Trigger Times | 0.2-0.6 sec super fast trigger times |
| Low Battery Auto Power Off | support |
| Triggering Interval | 5second ~ 60mins (default 60 sec) |
| Date Time Imprint | Yes |
| Moon Phase Imprint | Yes |
| Ambient Temperature Imprint | Yes |
| Serial NO. Imprint | Yes |
| Exposure | Auto |
| Pass Word Set | 4 bit, Digits and 26 alphabet set by yourself |
| Device Serial No. Set | 4 bit, Digits and 26 alphabet set by yourself |
| Time Switch | support |
| Periodic shot | 0Second~24Hours |
| Stand-by current | Lower than 0.2mA |
| Stand-by Time | Approx 8 months |
| Buid-in MIC | Yes |
| Buid-in Speaker | Yes |
| Interface | External: TV out (NTSC/PAL,MiniUSB); MiniUSB; SD Card Holder; 6V DC Power Jack |
| Fix Method | Bandage, Iron Bracket (1/4 Inch Standard Interface) |
| Operation Temperature | -20 - 60°C |
| Operating humidity | 5% ~ 90% |
| Power Source | 4-8 AA Battery DC :6V-1.5A |
| Water proof Standard | IP56 |
| Language | English/Deutsch/Dansk/Suomi/Svenska/Espanol/ Francais/Italiano/Nederlands/Portugues/Chinese |
| Security authentication | CE, ROHS |

Packing

| | |
|---------------------|-----------------|
| Product size | 136 x 98 x 76mm |
|---------------------|-----------------|

| | | |
|--|--------------------------|--|
| | Color box size | 180*122*104mm |
| | Net weight | 270g |
| | Shipment box size | 20个/CT 37.5*31.8*43.5cm |
| | Accessories list | MiniUSB Cable , Audio&Video Cable, Instructions, Iron Bracket, Bandage |

